



P.O. BOX 5187
303-708-8000

ENGLEWOOD, CO 80155-5187
FAX 303-708-8222 800-525-7058



SPECIFICATION SHEET FOR BANWEAR style 700-T

FABRIC: BANWEAR® STYLE 700-T
88% COTTON / 12% NYLON TWILL

WIDTH: 60/61"

THREAD COUNT: 94 X 50 THREADS PER SQUARE INCH

WEIGHT: 7.0 oz. PER SQ. YARD (Minimum)
(ASTM D3776-96)

BREAKING STRENGTH: 115 lbs. WARP (Minimum)
(ASTM D5034) 75 lbs. FILL (Minimum)

TEARING STRENGTH: 4.0 x 4.0 lbs. (Minimum)
(ASTM D1424)

SHRINKAGE: 5.0% MAXIMUM WARP & FILL OVER THE LIFE
(AATCC 96-1997) OF THE GARMENT

FLAMMABILITY: FEDERAL TEST METHOD 191
STANDARD METHOD 5903.1
AFTER FLAME: 2.0 SECONDS (Initial)
2.0 SECONDS (After 3 Launderings)
CHAR LENGTH: 4.0 INCHES (Maximum)

CARE INSTRUCTIONS: MACHINE WASH HOT WITH DETERGENT
NO CHLORINE BLEACH - NO SOAP
TUMBLE DRY WARM
DRY CLEANABLE

**THIS FABRIC MEETS THE INDUSTRY STANDARDS AS OUTLINED IN
ASTM F1506, NFPA70E HRC/2, NFPA1975, NFPA2112, and OSHA 29 CFR 1910.269**

*PROVIDED THE CARE INSTRUCTIONS ARE PROPERLY FOLLOWED, THE FINISH IN THIS
FABRIC IS DESIGNED TO LAST THE USABLE LIFE OF THE GARMENT*



ELECTRIC ARC PERFORMANCE VALUES ON SINGLE LAYER BANWEAR

<u>Fabric Style</u>	<u>Fabric Weight oz/yd²</u>	<u>ATPV Cal/cm²</u>
BANWEAR STYLE 700-T	7.5 oz.	9.6
BANWEAR STYLE 900-T	9.5 oz.	11.2

BANOX CERTIFIED

ELECTRIC ARC PERFORMANCE VALUES ON SINGLE LAYER BANOX CERTIFIED

<u>Fabric Style</u>	<u>Fabric Weight oz/yd²</u>	<u>ATPV Cal/cm²</u>
BANOX CERTIFIED STYLE 700-T	7.8 oz.	8.3
BANOX CERTIFIED STYLE 900-S	9.6 oz.	9.4
BANOX CERTIFIED STYLE 1400-T	14.1 oz.	14.8

**TESTING WAS CONDUCTED AT KINECTRICS INC.
TORONTO, CANADA**