



2845 W. 48TH PLACE  
CHICAGO, ILLINOIS 60632  
PHONE (773) 523-7000  
FAX (773) 523-0965  
www.westexinc.com

### SPECIFICATION

<b>FABRIC:</b>	<b>Style 391 INDURA<sup>®</sup> Ultra Soft<sup>®</sup> 88% Cotton/12% High Tenacity Nylon Denim</b>
<b>WIDTH</b> – (Inches, Minimum, Selvedge included): ASTM D3774	59
<b>YARNS PER INCH</b> – (Minimum, Warp and Fill): ASTM D3775	60 x 42
<b>WEIGHT</b> – (Oz/sq yd, Minimum): ASTM D3776	12.0
<b>BREAKING STRENGTH</b> – (Pounds, Minimum, Warp and Fill): ASTM D5034	190 x 100
<b>TEARING STRENGTH</b> – (Pounds, Minimum, Warp and Fill): ASTM D1424	9.5 x 6.5
<b>SHRINKAGE</b> – (% , Maximum): Federal Test Standard 191A Method 5550 Warp and Fill	3.0
<b>FLAMMABILITY:</b> ASTM D6413	
After Flame, Seconds (Maximum)	2.0
Char Length, Inches (Maximum)	5.0

This fabric meets the requirements of ASTM F1506, NFPA 70E Level 2,  
and OSHA 29 CFR 1910.269.

**INDURA<sup>®</sup> and INDURA<sup>®</sup> Ultra Soft<sup>®</sup>** are trademarks of Westex Inc.